

Tango LED G2



คุณสมบัติ

- Energy saving: system efficacy reaches >100lm/w, which gives more than 50% of energy saving when compared to conventional floodlight
- Free from lamp replacement: Lifetime reaches 50,000 hours at L70, which requires no lamp replacement after installation
- Low maintenance cost: IP65 housing ensures low maintenance with no need for internal cleaning, resulting in a lower total cost of ownership
- Flexibility on lighting application: Optical beam choice of symmetric and asymmetric fulfils majority needs of lighting application
- Good reliability: Painted non-corrosive die-cast aluminum housing and steel bracket gives extra strength when the luminaire is installed in a rough environment
- Easy installation and maintenance: Universal "U" shape mounting bracket.



Tango LED G2

ข้อมูลจำเพาะ Tango LED G2

รายการสินค้า	BVP281	BVP282	BVP283
Product Type	Flood Light		
Lumen output	4,000-12,000lm	17,600-22,000lm	21,000-35,500lm
Watt	40W-120W	160W-200W	210W-350W
Input	220-240V 50Hz		
Power Factor	0.95		
Weight	6.5kg	12kg	13.5kg
Material	Housing: Die-cast aluminum (ADC1) Gasket: Heat resistant silicone rubber Glass: Tempered glass Housing Colour: Grey Aluminium RAL9007		
Efficacy	>100lm/W		
CCT	5700K +/- 500K / 4000K +/- 500K / 3000K +/- 500K		
CRI	>75		
Classifications	IP65; IK07; Class I		
Control	Optional - DALI & 1-10V Dimming (ETO)		
Surge protection	10KV		
Lifetime	50,000 hrs (L70 @ Ta = 35°C)		
Working Temperature	-40oC to 45oC (Outdoor)		

Tango LED G2

BVP281 LED44 40W 220-240V

BVP281 LED88 80W 220-240V

BVP281 LED132 120W 220-240V

BVP282 LED176 160W 220-240V

BVP282 LED205 200W 220-240V

BVP283 LED210 210W 220-240V

BVP283 LED224 245W 220-240V

BVP283 LED280 280W 220-240V

BVP283 LED293 315W 220-240V

BVP283 LED340 335W 220-240V

BVP283 LED327 350W 220-240V

Mounting Instruction

